



AERIS

PENDANT

Inspired by the ethereal beauty of clouds, Aeris embodies softness and lightness through the repetition of sculptural forms, crafting an ethereal centerpiece. Each mouth blown glass cloud is paired with architecturally crafted brass bars that cross and lightly kiss together, evoking a sense of weightlessness—as if suspended in air.

The duality of the brass structural element defines each piece, with dual vertical drops playfully interacting with horizontal crossings, creating a unity to the entire fixture.

AVAILABLE FINISHES




TECHNICAL

MATERIAL	TREATED BRASS, GLASS	
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.	
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) 8W, 800LM, 2700K	
DIMMING	WATTAGE AND LUMEN OUTPUT WILL VARY SLIGHTLY DEPENDING ON CONSTANT CURRENT OUTPUT.	
	220-240V REGION	
	PHASE	DIMMING RANGE 5 - 100%
	DALI	DIMMING RANGE 1 - 100%
	110-120V REGION	
	PHASE	DIMMING RANGE 3 - 100%
	DALI	DIMMING RANGE 0.1 - 100%
LED LIFESPAN	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.	
	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	
	50,000 HRS	
IP RATING	IP20 - FOR INDOOR USE ONLY	
CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 ETL/UL CERTIFICATION PENDING
CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE	

DRIVER SIZE	220-240V PHASE 220-240V DALI 110-120V TRIAC 110-120V DALI	L101 X W49 X H29 / L4" X W2" X H1.1" L145 X W30 X H21 / L5.7" X W1.2" / X H0.9" *L75 X W35 X H26.5 / L3" X W1.4" X H1" *L75 X W35 X H26.5 / L3" X W1.4" X H1"
SKU CODES	*DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX.	
	EG. AEP-G-WHT.BR-BRZ AERIS PENDANT IN WHITE GLASS WITH A BRONZED BRASS FRAME	
	AE104.G-XXX.BR-XXX	
PRODUCT WEIGHT	GLASS	
	FROSTED BLACK (G-FBL) BLACK (G-BLK) WHITE (G-WHT) CLEAR (G-CLR)	
	FRAME	
PACKAGE WEIGHT	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)	
	4KG / 8.8LB	
	5KG / 11LB	
PACKAGE SIZE	1 X L 620 W 320 H 320 / L 24.4" W 12.6" H 12.6"	

DIMENSIONS



L 245 W 245 H 155  
L 9.6" W 9.6" H 6.1"  
MIN DROP HEIGHT - H 400 / 15.7"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED.



SLIM  
Ø14MM DOUBLE CANOPY  
CAN.SL.F14.XX-XXX  
  
Ø120 X 7MM / 4.7" X 0.3"  
  
DRIVER HOUSED IN CEILING  
OR JUNCTION BOX



PUCK  
Ø14MM DOUBLE CANOPY  
CAN.PK.D14.XX-XXX  
  
Ø50 X 65MM / 2" X 2.6"  
  
DRIVER HOUSED IN CEILING



LARGE  
Ø14MM DOUBLE CANOPY  
CAN.ST.170.F14.XX-XXX  
  
Ø170 X 40MM / 6.7" X 1.6"  
  
DRIVER HOUSED IN CANOPY

TECHNICAL

MATERIAL	TREATED BRASS
CANOPY FINISH	<div><div>BRUSHED BRASS</div><div>BLACKENED BRASS</div><div>BRONZED BRASS</div></div>
	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)
SKU CODES	EG. CAN.SL.D14.BR-BLK = SLIM DOUBLE CANOPY IN BLACKENED BRASS FINISH

\*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION.  
\*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.