



# XSIGHT LABS E-SERIES E1

## 800 GE Infrastructure Processor with Linux Data Plane for the Hyperscale Cloud and Edge

### OVERVIEW

The Xsight Labs E1 Infrastructure Processor is a highly integrated compute, networking, and storage platform, designed for cloud and data center infrastructure workloads.


Featuring the industry’s only programmable Arm®-based data plane DPU, with up to 64 N2 cores, the E1 integrates 800 Gbps of accelerated networking, wire-speed inline security, storage offloads, and a customizable PCIe fabric.

The E1 is supported by an open, standards-based, and extensible programming model.

The E1 integrates a high speed coherent-interconnect and 32 MB of internal RAM, presented as a configurable mix of latency-deterministic direct-mapped memory and DRAM-backed system level cache, passing every packet through the E1 processing array, while supporting large control structures.

Its scalable, multi-core architecture brings a standard software development model to DPUs and allows for unified, coherent, control and data planes. Native support for in-kernel and user-space networking frameworks such as XDP and DPDK/SPDK democratizes SDN and SDS feature development and portability.

As a host, the E1 delivers best-in-class performance per watt and TCO metrics for memory intensive, scale-out workloads associated with edge cloud architectures.



# TARGET APPLICATIONS

## Cloud Data Center, Infrastructure Edge

### Networking, Storage, and Security

- Multi-host optimized Smart-NIC with flexible buffering
- AI/ML/HPC RDMA, local/remote storage connectivity
- Smart Switch DPU architectures supporting up to 200 Mpps and 20M connections per second
- Data path offload for virtual switching in bump-in-wire configurations
- Full hypervisor offload and bare metal provisioning
- Full stack offload for NVMe-oF and NVMe/TCP storage initiator and target
- TLS/DTLS Termination with TCP and QUIC Proxy
- Scalable, full featured TLS/kTLS offload
- Stateful distributed firewall architectures

### Edge Compute Platform

- Up to 4x improvement in performance/watt for memory-intensive, scale-out edge workloads
- Fully integrated computational storage node
- CDN/WebServer, distributed software load-balancer

# FEATURES

### Compute and Memory

- Up to 64 Arm Neoverse N2 v9.0-A cores
- 32MB of internal RAM, presented as System Level Cache or direct-mapped memory, with NUMA and MPAM support.
- Up to 4 DDR5 at 5200 MT/s supporting 166GB/sec bandwidth and full inline memory encryption with AES-XTS
- High Speed coherent interconnect

### Programmable PCIe Fabric

- 32 PCIe Gen5.0 lanes, 8 dual-mode controllers
- PCIe configuration space emulation
- Software based MMIO space emulation
- SR-IOV with up to 64K PF/VFs and scalable IOV
- Up to 4 hosts/device
- Peer-to-peer PCIe switching with address translation

### Accelerated Networking, Storage and Security

- Up to 800 Gbps networking throughput with eight 112/56/25/10G SerDes
- 2x400G, 4x200G or 8x100G/50G/25G/10G port configurations
- Protocol-independent programmable parser and multi-stage exact match lookup with DRAM-backed tables
- Line rate AES-GCM network crypto supporting IPsec ESP and UDP SEC
- Software-activated 3 Tbps DMA engines with cache stashing
- Stateless offloads: Checksum, RSS, TSO, RoCEv2 iCRC
- Line rate block storage crypto with AES-XTS
- Storage Protection Information offloads including T10-DIF/DIX, CRC GMAC and SHA2/3, and scrub CRC

### Open, Standards-based, Extensible Software

- UEFI Secure boot with Arm Trusted Firmware (TF-A)
- Arm SystemReady certification for running unmodified Linux distros
  - + Debian, Ubuntu, SONiC, Lightbits Labs LightOS™
- Linux Netdev, VirtIO and Xsight Network Adapter (XNA) drivers
- Custom SDN data planes with Linux, XDP and DPDK/SPDK programming models
- Infrastructure software and reference applications
  - + Emulated NVMe, RDMA and Network devices as DPDK/SPDK applications
  - + SONiC with DASH data plane
  - + Virtual Switch, RoCEv2

### Secure Management

- 8 PCIe Gen5.0 management lanes, 2 dual-mode controllers
- 2 x 1 GbE for out-of-band provisioning
- Arm-based firmware processor with UEFI secure boot, hardware root-of-trust
- I2C/I3C/SMBus, SPI/QSPI and SMI interfaces
- UART, GPIO, 1588 RTC, JTAG interfaces

# E1 SYSTEMS

Xsight Labs E-Series solutions are available in multiple form factors, depending on deployment needs.

As a discrete solution, the E1 devices can be deployed as DPUs to handle distributed services, or as a host for scale-out.

The Xsight Labs E1-Server is a 1RU compute system with 800G of integrated network, optimal for edge-compute workloads.

The Xsight Labs E1-AIC is a full-height, 3/4 length PCIe add-in-card with 800G networking, optimal for host attached deployments.

For more information on the E-Series system, refer to the E1-Server and E1-AIC Product Briefs.

## E-SERIES FEATURE TABLE

The E1 product family is offered in different variations all sharing the same software and feature-set and interoperability. For additional product information, contact [sales@xsightlabs.com](mailto:sales@xsightlabs.com).

Feature	E1-32	E1-64
Arm Cores	32	64
System Level Cache	16 MB	32 MB
Memory	2 x DDR5-5200 MT/s	4 x DDR5-5200 MT/s

**Copyright © 2017-2025 Xsight Labs LTD.** All Rights Reserved. THE INTELLECTUAL AND TECHNICAL CONCEPTS AND INFORMATION (“**INFORMATION**”) CONTAINED HEREIN ARE PROPRIETARY OF XSIGHT LABS LTD. (“**XSIGHT**”) AND ITS LICENSORS AND MAY BE PROTECTED OR GOVERNED BY VARIOUS PATENTS, PATENTS IN PROCESS, TRADEMARKS, TRADEMARKS IN PROCESS, AND ARE PROTECTED BY TRADE SECRET OR COPYRIGHT LAW. DISSEMINATION, REPRODUCTION OR OTHER UNAUTHORIZED USE OF THIS INFORMATION IS STRICTLY FORBIDDEN UNLESS PRIOR WRITTEN PERMISSION IS OBTAINED FROM XSIGHT. YOU MAY ONLY COPY, MODIFY, DISTRIBUTE, DISPLAY, LICENSE, OR SELL THE CONTENT IF YOU ARE GRANTED EXPLICIT PERMISSION SUCH AS WITHIN A WRITTEN AGREEMENT WITH XSIGHT OR OTHER WRITTEN TERMS BY XSIGHT THAT ACCOMPANY THE CONTENT. ALL INFORMATION CONTAINED HEREIN IS, AND REMAINS THE SOLE PROPERTY OF, XSIGHT AND ITS LICENSORS (AS APPLICABLE). XSIGHT RESERVES THE RIGHT TO MAKE CHANGES TO THE INFORMATION.