



B (1 : 10)

Torque: 2500Nm

E (1 : 10)

Notes:
Apply "Loctite 2700" to all threaded connections

PARTS LIST						
ITEM	QTY	PART NUMBER	TITLE	Material	Dimensions	MASS
1	1	10040-200	Common tower tool, welded	-	-	1701,6 kg
2	8	10040-408	Plate for bolt interface	S690Q EN 10025-6	Plate 45mm	14,5 kg
3	4	10040-426	Support bracket for tower section 1	S355J2 EN 10025-2	Plate 50mm	159,2 kg
4	1	10040-427	Support bracket for tower section 2	S355J2 EN 10025-2	Plate 50mm	158,7 kg
5	1	10040-430	Support bracket for tower section 3	S355J2 EN 10025-2	Plate 50mm	158,7 kg
6	2	10040-417	Bonded foam 230kg/m3	Bonded foam 230kg/m3	1710x150x50mm	10,3 kg
7	6	ISO 4014 - M36 x 260				2,5 kg
8	6	ISO 4032 - M36				0,4 kg
9	12	DIN 125-1 - B 37				0,1 kg
10	8	ISO 4017 - M16 x 40				0,1 kg
11	20	DIN 125-1 - B 17				0 kg
12	8	ISO 10511 - M16	Lock Nut			0 kg
13	1	10040-424	Support bracket (right) for SGRE flange D1012633	S355J2 EN 10025-2	Plate 20mm	15,8 kg
14	1	10040-433	Support bracket (left) for SGRE flange D1012633	S355J2 EN 10025-2	Plate 20mm	15,8 kg
15	2	ISO 4014 - M16 x 100				0,2 kg
16	2	ISO 4032 - M16				0 kg
17	1	Equipment Label				0 kg

Designed by: APE
Date: 17-02-2019

Dimensions: 4500x900x405mm
Material: -

Coating: -
Class: -

Projection:

Description:
Common tower tool, assembled

Rev. no.: 7

Format: A3

Scale: 1 : 20

Sheet no.: 1 / 1

Drawing no.: 10040-001

Weight: N/A