

Number: BURL-088
Creation Date: 12/19/2017
Revision Date: 09/22/2022
Created by: Legal Dept.

UMBRELLA AND UMBRELLA STANDS

| TEST DESCRIPTION | REGULATION/TEST METHOD | REQUIREMENTS |
|---|--|--|
| MANDATORY | | |
| Label Verification | F.P. & L. Act (16 CFR 500) OR NIST Uniform Laws and Regulations Handbook 130 | Manufacturer, packer, or distributor's name & address (city, state & zip) |
| | | Product Identification Net quantity of contents shall be expressed in terms of weight or mass, measure, numerical count, or combination so as to give accurate information to facilitate consumer comparison (U.S. and metric units). |
| Country of Origin Marking | 19 CFR 134.11 | Shall indicate country of origin legibly, permanently, and incomparable size and close proximity to any mention of country other than country in which the article was manufactured or produced. Must be visible at point of purchase. |
| Fiber analysis | AATCC 20/20A | Single Fiber: No tolerance Blended Fiber: +/- 3% |
| Formaldehyde Emission (Composite Wood Component only) | Federal Toxic Substances Control Act, 15 U.S.C., Sec. 2697 (TSCA Title VI). and California Health & Safety Code (title 17, sections 93120 – 93120.12). | Finished product must be labeled "TSCA Title VI compliant" or "TSCA TITLE VI and NAF/ULEF Compliant" with manufacturer's name and date the finished good Formaldehyde emission requirements: HWPW-VC: ≤0.05 ppm HWPW-CC: ≤ 0.05 ppm PB: ≤ 0.09 ppm MDF: ≤ 0.11 ppm Thin-MDF: ≤ 0.13 ppm |
| STATES REGULATIONS | | |
| California Prop 65 | Warning label or applicable testing | In lieu of warning label, product should meet all applicable Prop 65 requirements. |
| Total heavy metals in packaging | Toxics in Packaging Clearinghouse (TPCH) | Packaging shall not contain the sum of mercury, cadmium, lead and chromium (VI) in concentration above 0.01% by weight. |
| Plastic Bag Warnings | Various state laws | Plastic bags with a thickness of less than 1 mil (0.001 inch) having an opened end larger than 5 inches in diameter shall contain the following warning statement or equivalent: WARNING: To avoid danger of suffocation, keep this plastic bag away from babies and children. Do not use this bag in cribs, beds, carriages or playpens. This bag is not a toy. |
| OPTION (QUALITY & PERFORMANCE) | | |
| Sharp Points / Edges | 16 CFR 1500.48 / 1500.49 | Shall have no sharp points or edges as received, other than those required for function. |
| Resistance to Corrosion (For metal component) | ASTM B117 | Metal component shall withstand 24 hours in 5% salt spray (fog) with no major corrosion |
| Colorfastness to Light (For fabric of outdoor use article) | AATCC 16.3 (80 AFU) | For fabric of outdoor use article: Grade 4 min. |
| Colorfastness to Crocking (For fabric) | AATCC 8 / 116 | Dry: Grade 4 min. Wet: Grade 3 min. |

| TEST DESCRIPTION | REGULATION/TEST METHOD | REQUIREMENTS |
|---|------------------------|---|
| Water Repellency - Spray Test (For fabric) | AATCC 22 | Original: Rating 90 min. After wash (if request): Rating 70 min. |