

PILLOWS (INCLUDING DECORATIVE AND FUNCTIONAL PILLOWS)

(Adult and Children's Over 3 Years of Age)

Number: BURL-004
Creation Date: 12/19/2017
Revision Date: 9/16/2022
Created by: Legal Dept.

TEST DESCRIPTION	REGULATION/TEST METHOD	REQUIREMENTS
MANDATORY		
Label Verification Fiber Content Country of Origin Registration Number (RN) or Wool products Registration Number (WPL)	All Federal & State Requirements 16 CFR 303 16 CFR 300 19 CFR 134	Must Comply
Law Label for filling materials	Must Comply	Meet all states requirements with state registration number and active registration
Real Fur / Faux Fur	Visual/ Massachusetts General Laws Part I Chapter 94 Section 277a/ New York State General Business Law Section 399-AAA/ Delaware Title 6 Chapter 25/ New Jersey Title 56. Chapter 14. (New) Fur Products §§1-3 - C.56:14-1 to 56:14-3/ 16 CFR 301	Massachusetts-All natural, dyed or imitation furs, and all articles made wholly or partly therefrom, sold at retail within the commonwealth, shall be plainly marked or labelled with an accurate statement of the material which they contain, together with the name and address of the seller. For Clothing sold in New York via stores, catalog and internet containing faux fur: Faux fur should be listed on a permanent label, or a temporary tag or a sticker. 16 CFR 301, other states law in real fur: refer to regulation for details
Fiber Content	AATCC 20/20A	Single fiber ± 0.0% Blends ± 3.0%
Package Label Verification	F.P. & L. Act (16 CFR 500) OR NIST Uniform Laws and Regulations Handbook 130	Manufacturer, packer, or distributor's name & address (city, state & zip)
		Product Identification Net quantity of contents shall be expressed in terms of weight or mass, measure, numerical count, or combination so as to give accurate information to facilitate consumer comparison (U.S. and metric units).
California Prop 65	Warning label or applicable testing	In lieu of warning label, product should meet all applicable Prop 65 requirements.
Pentachlorothiophenol (PCTP)	Environmental Protection Agency, 86 FR 894, Final Rule, 40 CFR Part 751, Subpart E	≤ 1 % (10000 mg/kg)
Hexachlorobutadiene (HCBD)	Environmental Protection Agency, 86 FR 894, Final Rule, 40 CFR Part 751, Subpart E	Prohibited

Flammability and Flammability Labeling (Floor pillows/ cushions and decorative pillows greater than 25 inches in any dimension)	California TB 117-2013/ 16 CFR 1640	Must Comply Apply to pillow or cushion that can be used as a support for the body or limbs when sitting or resting in an upright or reclining position. Please refer to the specific regulations for exempted products
--	--	--

ADDITIONAL MANDATORY TESTS FOR CHILDREN'S PRODUCT

Total Lead Content in Substrate Material	CPSC-CH-E1001-08.3 (metallic substrates) CPSC-CH-E1002-08.3 (nonmetallic substrates)	≤100 ppm - Exclude mill-dyed and mill printed fabrics and threads. - Exclude Natural material in natural state, treated without added lead or substrate with coating removed e.g. leather or fur	
Total Lead in Surface Coating	16 CFR 1303	≤ 90ppm All accessible coating	
Sharp Points/Sharp Edges (under 8 years of age)	16 CFR 1500.48/49	Not allowed	
Tracking labels for children's products	Consumer Product Safety Improvement Act of 2008	A permanent and distinguishing mark on the product and its packaging, to the extent practicable, enabling the manufacturer and purchaser to ascertain the name of the manufacturer or private labeler, location and date of production of the product.	
Washington lead, cadmium and phthalates on children's product	Washington Children's Safe Products Act (CSPA)	≤40 ppm Cadmium; ≤90 ppm Lead; ≤1000 ppm Phthalates (combined).	
New York Toxic chemicals in children's products	The Toxic Free Toys Act (Albany, Suffolk County)	Compound	Max. levels in ppm
		Antimony	60 (soluble)
		Arsenic	25 (soluble)
		Cadmium	75 (soluble)
		Lead in surface coating	90 (soluble)
		Lead in substrates	100 (total)
		Mercury	60 (Soluble)

STATES REGULATIONS

Total heavy metals in packaging	Toxics in Packaging Clearinghouse (TPCH)	Packaging shall not contain the sum of mercury, cadmium, lead and chromium (VI) in concentration above 0.01% by weight. Sum of Phthalates: ≤ 100 mg/kg PFAS: Not detected
Plastic Bag Warnings	Various state laws	Plastic bags with a thickness of less than 1 mil (0.001 inch) having an opened end larger than 5 inches in diameter shall contain the following warning statement or equivalent: WARNING: To avoid danger of suffocation, keep this plastic bag away from babies and children. Do not use this bag in cribs, beds, carriages or playpens. This bag is not a toy.
Flame Retardants	Various state laws	Products claimed with flame retardant treatment shall meet all applicable requirements.
Chemicals of High Concern for Children / Priority Chemicals	Various US States Law	Record the concentration of Chemicals of High Concern for Children / Priority Chemicals. No pass / fail verdict.

OPTION (QUALITY & PERFORMANCE)

Care Labeling	FTC regulation	Must Comply
Formaldehyde (Spot Test)	AATCC 94	No Trace If trace is found - proceed with full testing

Formaldehyde	JIS 1041 LAW 112 ISO 14184-1 (textile) ISO 17226-1 (leather)	Adult: <75 ppm Children: <20 ppm -Direct skin contact: 75 mg/kg -Without direct skin contact: 300 mg/kg
pH of Water Extract	AATCC TM81 (textile) ASTM D2810 (leather)	Textile: 4.0-8.0 Leather: 3.5-7.5
General Appearance After Laundering 3 Home Launderings/1 Drycleaning	Visual Evaluation	- No open raveling, open seams, or tufting damage. - No obvious defects/observations affecting the end product performance/appearance. - Color Change /Self staining: Grade 4 List all observations
Dimensional Stability	AATCC 150 / 158	3 Home Laundering/1 Drycleaning Shrinkage: -3.5% x -3.5% Max. Growth: +1% x +1% Max.
Torque (Knits only)	AATCC 179 Method 2, Option 3	5.0% Max
Colorfastness to Laundering/ Dry Cleaning	AATCC 61/132	Shade Change: Grade 4 minimum Staining: Grade 3 minimum Self –Staining: Grade 5/ No Self Staining
Colorfastness to Crocking	AATCC 8/116	Dry: Grade 4 minimum Wet: Grade 3 minimum
Colorfastness to Non-Chlorine Bleach	AATCC TS 001	Grade 4 minimum
Tensile Strength (Wovens)	ASTM D5034	40 x 25 lbs. (warp x weft)
Tear Strength (Wovens)	ASTM D1424	3.0 x 2.5 lbs. (warp x weft)
Seam Strength(Wovens)	ASTM D 1683	Across Each Seam:: 20 lbs. Minimum Bartacks and reinforcements: 20 lbs. Min
Pilling Resistance Martindale Pilling Method 100 Movements	ASTM D4970	Grade 3.5 minimum
Attachment Strength Snaps Buttons, Shanks, Rivets, etc. Hand-Sewn Beads, Sequins, etc.	ASTM D7142 Opt. 2 16 CFR 1500.50-53 16 CFR 1500.50-53	15 lb. / 10 sec. 15 lb. / 10 sec. 5 lb. / 10 sec