

Number: BURL-007

Creation Date: 12/19/2017

Revision Date: 9/16/2022

Created by: Legal Dept.

SHOWER CURTAINS (Adult)

TEST DESCRIPTION	REGULATION/TEST METHOD	REQUIREMENTS
MANDATORY		
Label Verification	F.P. & L. Act (16 CFR 500) OR NIST Uniform Laws and Regulations Handbook 130	Manufacturer, packer, or distributor's name & address (city, state & zip)
		Product Identification
		Net quantity of contents shall be expressed in terms of weight or mass, measure, numerical count, or combination so as to give accurate information to facilitate consumer comparison (U.S. and metric units).
Sew-in Label Verification - Fiber Content - Registration Number (RN) or Wool products Registration Number (WPL) (for Textile Shower Curtains)	All Federal & State Requirements 16 CFR 303 16 CFR 300	Must Comply
Country of Origin Marking	19 CFR 134.11	Shall indicate country of origin legibly, permanently, and incomparable size and close proximity to any mention of country other than country in which the article was manufactured or produced. Must be visible at point of purchase.
Fiber analysis (textile only)	AATCC 20/20A	Single Fiber: No tolerance Blended Fiber: +/- 3%
California Prop 65	Warning label or applicable testing	In lieu of warning label, product should meet all applicable Prop 65 requirements.
Pentachlorothiophenol (PCTP)	Environmental Protection Agency, 86 FR 894, Final Rule, 40 CFR Part 751, Subpart E	≤ 1 % (10000 mg/kg)
Hexachlorobutadiene (HCBD)	Environmental Protection Agency, 86 FR 894, Final Rule, 40 CFR Part 751, Subpart E	Prohibited
STATES REGULATIONS		
Total heavy metals in packaging	Toxics in Packaging Clearinghouse (TPCH)	Packaging shall not contain the sum of mercury, cadmium, lead and chromium (VI) in concentration above 0.01% by weight. Sum of Phthalates: ≤ 100 mg/kg PFAS: Not detected
Flame Retardants	Various state laws	Products claimed with flame retardant treatment shall meet all applicable requirements.
OPTIONAL (PERFORMANCE & QUALITY) MANDATORY		
Sharp Points / Edges	16 CFR 1500.48 / 1500.49	Shall have no sharp points or edges as received, other than those required for function.
Resistance to Corrosion (For metal component)	ASTM B117	Metal component shall withstand 24 hours in 5% salt spray (fog) with no major corrosion
Colorfastness to Crocking (For fabric)	AATCC 8 / 116	Dry: Grade 4 min. Wet: Grade 3 min.

Colorfastness to Water (For fabric)	AATCC 107	Color Change: Print and pigment: 3.5 min., others 4 min. Color Staining: Print and pigment: 3.5 min., others 4 min. Self-staining: 4.5 min.
Water Repellency - Spray Test (For fabric) – if claimed	AATCC 22	Original: Rating 90 min. After wash (if request): Rating 70 min.
Water- Resistant- Rain test (For fabric) – if claimed	AATCC 35	Max. 1 gram