

DECORSLOT®
-BUILD YOUR
SPECIFICATION

Complete the table and use the details in
your project specification.

PRODUCT	DECORSLOT	SUPPLIER	DECOR SYSTEMS - PH: 1800 835 035
PROFILE	(CHOOSE A PROFILE FROM THE LIST ABOVE)		
FINISH	(CHOOSE A FINISH FROM THE LIST ABOVE)		
FINISH VARIATION	(E.G. SMARTLOOK COLOUR)		
SUBSTRATE	6MM FIBRE CEMENT	9MM FIBRE CEMENT	
FIXING METHOD	WALL VISIBLE - FACE FIXED/DIRECT FIX	CEILING VISIBLE - FACE FIXED/DIRECT FIX	CEILING CEILING GRID - DROP-IN TILE
BIOPANEL ZAP-X	YES	NO	
DECORINSUL	YES	NO	
FIRE CERTIFICATION	DECORSLOT® COMES WITH A GROUP 1 FIRE RATING AND IS DEEMED NON-COMBUSTIBLE		
NOTES	(ANY EXTRA INFORMATION YOU WOULD LIKE TO ADD?)		
<p>This product requires an air gap and DecorInsul behind the panels for the best acoustic performance. Consult the acoustic test results, and opinion of project acoustic engineer for more details. If not available due to site constraints or budget, a 50mm gap with DecorInsul works in most cases.</p> <p>Close collaboration between Decor Systems, the project architect and the client has taken place to develop this specification. DecorSlot® cannot be substituted unless agreed by Architect and Acoustic Engineer.</p> <p>Decor Systems certificate # (Contact your Decor Systems project consultant for your individual project number) to be supplied upon completion.</p> <p>Panel installation to be as per manufacturer's instructions and AS/NZS 2785. - Installation to be done by an approved ceiling and partition contractor.</p> <p>Product guarantee to be 99 years as per Decor Systems guarantee. Please contact Decor Systems for your project specific completion number.</p>			

