


T-ZERO^{PRO}

POWER & INNOVATION



HYBRID
technology



LITHIUM
battery

STAGE 5
CERTIFIED



YANMAR



1500
RPM



WATER
cooled



DIESEL



SINGLE
phase



THREE
phase



MGTP 24000/30 TH LITHIUM 3P

Code **RP314-7TS4**

Features

Outlet socket	2 x 32A - 400V 2 x 63A - 400V
Inlet plug	63A - 400V
Inverter	3 x 48V/8000VA
Battery charger	11.5kW

Alternator

Model	Linz PRO 18M E/4
Rated output	20kVA
Frequency	50Hz
Voltage	400V
Insulation class	H
Degree of Protection	IP23

Engine

Model	YANMAR 4TNV88
Fuel	Diesel
Engine speed	1500rpm
Noise level at 7mt	65dBA
Emissions regulations	STAGE 5

Consumption only engine mode

Tank capacity	250lt
Fuel consumption - Running time	5,9 l/h -42,4 hrs

Lithium Batteries

Battery	25,6V - 280Ah
Batteries number	4
Battery Pack	51,2VDC-28.7kWh
Expected battery cycle	3500 - 80% DOD

Dimensions & Weight

Dimension	2441 x 1131 x 1920 mm
Weight	1710Kg

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310 / COMAP MRS16	Fuel level monitor
ON/OFF switch	Emergency stop
Earth leakage circuit breaker	

Distribution Panel

2x32A-400V + 2x63A-400V outlet socket
1x63A-400V inlet plug
1x32A RVS inlet plug for additional solar panels

Standard Features

Main circuit breaker	Spark arrestor
Earth leakage relay	Lockable control panel
Emergency stop	Digital tank float
Built in fuel tank c/w 3 ways valve	4G LTE Router
MG Master safety and control unit for the battery system	Cerbo GX Touch 50 monitoring display controller c/w Cerbo GX communication-centre
Sides Forklift pockets	4G Puck MIMO Omni Antenna
Exhaust gas silencer	Bunded tank
Soundproof canopy	

Continuous Inverter Output Power

24000VA

Overload (0,5 sec)

60000VA

Running Time with Constant Load from Batteries

5000W	4.6h
10000W	2.3h
15000W	1.5h

Recharging time - Power requested

2.8h	15.4kW
Max Loading during recharging time	0.6kW

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.